

Citrix Access Gateway Standard 4.x

Contents

- [1 Introduction](#)
- [2 Prerequisites](#)
- [3 Baseline](#)
- [4 Architecture](#)
- [5 Installation](#)
- [6 Swivel Configuration](#)
 - ◆ [6.1 Configuring the RADIUS server](#)
 - ◆ [6.2 Setting up PINsafe Dual Channel Transports](#)
 - ◆ [6.3 Citrix Access Gateway Standard Edition Integration](#)
- [7 Additional Information](#)

Introduction

This document covers the integration of Swivel with the Citrix Access Gateway Standard edition. The standard edition allows authentication using SMS, Email, Mobile Phone applet, PINsafe [Taskbar](#), but does not allow the single channel image to be embedded into the login page. To allow the single channel image to be embedded into the login page, the Advanced Access Controller is required, see [Citrix Access Gateway Advanced 4.x](#)

Prerequisites

Swivel 3.x

Citrix Access Gateway 4.x

Baseline

Architecture

Authentications are made against Swivel using RADIUS.

Installation

Swivel Configuration

Configuring the RADIUS server

On the Swivel Administration console configure the RADIUS Server and NAS, see [RADIUS Configuration](#)

Setting up PINsafe Dual Channel Transports

See [Transport Configuration](#)

Citrix Access Gateway Standard Edition Integration

Follow the Citrix Access Gateway Standard Edition Administration guide to configure RADIUS authentication.

Additional Information

For additional features use the Advanced Access Controller. This allows customised login pages and the Single Channel Turing Image authentication, see [Citrix Access Gateway Advanced 4.x](#)