

XML Authentication Configuration

Agent-XML Authentication Configuration

Overview

For non RADIUS devices, PINsafe supports an XML authentication as described below. For RADIUS authentication configuration see [RADIUS Configuration](#)

This Agent-XML configuration guide outlines how to configure PINsafe as a Agent-XML server for Agent-XML Client. For further information on the PINsafe Agent-XML server and options available see [Agent-XML](#)

Configuring the PINsafe Agent-XML server

Configure the PINsafe server by selecting which Agents are permitted to connect to the PINsafe server. To do this, on the PINsafe Administration Console select Server/Agents. Options available are:

Agents: Name: A descriptive Name of the agent permitted to connect

Hostname/IP: IP or Hostname of the agent

Shared secret: A shared secret that must also be entered on the Agent-XML client configuration

Group: Authentication by the agent can be restricted to a group of users

Authentication Modes: Authentication can be restricted to single or dual channel authentication

Name:	<input type="text" value="descriptive name"/>
Hostname/IP:	<input type="text" value="192.168.0.4"/>
Shared secret:	<input type="password" value="....."/>
Group:	<input type="text" value="---ANY---"/> ▼
Authentication Modes:	<input type="text" value="ALL"/> ▼
<input type="button" value="Delete"/>	