

# Appliance Proxy settings

## Configuring an application to use proxy authentication

*Configuration Notes*

### Contents

- 1 Introduction
  - ◆ 1.1 Proxy CMI Configuration
  - ◆ 1.2 Proxy Command Line Configuration
- 2 Testing
- 3 Known Issues
- 4 Troubleshooting
  - ◆ 4.1 Error Messages

## Introduction

Some communications may require a proxy connection to the internet.

### Proxy CMI Configuration

From the CMI select Advanced Options/Networking/HTTP Proxy then select Enter HTTP Proxy.

Enter the following information:

**Server:** The Proxy server IP or hostname

**Port:** The Proxy server port

**Username:** The username for authentication to the Proxy Port

**Password:** the password for authentication to the proxy port.

For the settings to take effect restart Tomcat.

### Proxy Command Line Configuration

For devices that do not have the CMI appliance Proxy configuration, it must be configured through the command line. To configure a proxy for communication from the Swivel appliance edit the following file

It is assumed that the appliance is already configured, and has a valid IP address on your network.

```
/etc/profile
```

Add the following lines:

```
export http_proxy=http://username:password@<wwwcacheaddress>:port
export ftp_proxy=http://username:password@wwwcacheaddress:port
export gopher_proxy=http://username:password@wwwcacheaddress:port
```

Example:

```
export http_proxy=http://user1234:pass1234@<www.swivelcache.com>:8080
```

## Testing

```
echo $http_proxy
```

For settings to take effect reboot the server.

If any error messages are reported please contact Swivel Secure support ([support@swivelsecure.com](mailto:support@swivelsecure.com)) for assistance.

## Known Issues

Appliance build 2.0.9a may not pass the authentication credentials to the proxy server

## Troubleshooting

### Error Messages

**LOG\_HTTP\_TRANSPORT\_ERROR, Unable to tunnel through proxy. Proxy returns "HTTP/1.1 407 Proxy Authentication Required"**

Authentication is required, enter authentication details. Verify authentication details are correct. Remember to restart Tomcat. It may require allowing access without authentication from the Swivel IP address.

**LOG\_HTTP\_TRANSPORT\_ERROR, No route to host**

Swivel may not be using the Proxy server, ensure correct details and Tomcat has been restarted. Ensure that the DNS name is recognised.