Citrix Access Gateway Standard 4.x

Contents

- 1 Introduction
- 2 Prerequisites
- 3 Baseline
- 4 Architecture
- 5 Installation
- 6 Swivel Configuration
    - 6.1 Configuring the RADIUS server
    - 6.2 Setting up PINsafe Dual Channel Transports
    - 6.3 Citrix Access Gateway Standard Edition Integration
- 7 Additional Information

Introduction

This document covers the integration of Swivel with the Citrix Access Gateway Standard edition. The standard edition allows authentication using SMS, Email, Mobile Phone applet, PINsafe Taskbar, but does not allow the single channel image to be embedded into the login page. To allow the single channel image to be embedded into the login page, the Advanced Access Controller is required, see Citrix Access Gateway Advanced 4.x

Prerequisites

Swivel 3.x

Citrix Access Gateway 4.x

Baseline

Architecture

Authentications are made against Swivel using RADIUS.

Installation

Swivel Configuration

Configuring the RADIUS server

On the Swivel Administration console configure the RADIUS Server and NAS, see RADIUS Configuration

Setting up PINsafe Dual Channel Transports

See Transport Configuration

Citrix Access Gateway Standard Edition Integration

Follow the Citrix Access Gateway Standard Edition Administration guide to configure RADIUS authentication.

Additional Information

For additional features use the Advanced Access Controller. This allows customised login pages and the Single Channel Turing Image authentication, see Citrix Access Gateway Advanced 4.x