

PINsafe PositiveID Server Patch

Contents

- [1 Overview](#)
- [2 Prerequisites](#)
- [3 Installation](#)
- [4 Verification](#)

Overview

This Patch covers some bugs present in some versions of PINsafe with relation PositiveID

Prerequisites

PINsafe 3.7.3474

[Patch File](#)

Installation

1. Stop Tomcat
2. Extract the contents of the file pinsafe.positiveid.patch and copy the folder WEB-INF to <path to Tomcat>/webapps/pinsafe overwriting any files where required. For further information on copying files see [Copying appliance files How to Guide](#). Ensure file permissions are correct, see [Permissions and Ownership](#)
3. Edit the file <path to Tomcat>/webapps/pinsafe/WEB-INF/languages/console.en.xml and insert the contents of the file language.xml, (either immediately after <Phrases>, or just before </Phrases>).
4. For PINsafe appliances, copy the file proxy.war to <path to Tomcat>/webapps2 overwriting the current proxy file.
3. Start Tomcat

Verification

Follow the instructions for configuring PositiveID, see [PositiveID How to Guide](#). On the PINsafe administration console, select User Administration, then left click on a user and ensure the PID button is visible (either greyed out or selectable). If it is not then the patch may not have installed correctly. Try a User Sync.